

Polynt SpA – Headquarter

Via Enrico Fermi, 51 I-24020 Scanzorosciate (Bg) Italy Tel. +39 035 652770

Fax +39 035 652814

Polynt SpA

Via Abate Bertone, 10 13881 Cavaglià (BI) Italy Tel. +39 01 61996611 Fax. +39 01 61996623 Polynt UK Ltd

Station Road - Cheddleton Nr Leek Staffordshire ST13 7EF UK Tel. + 44 1538 369000 Fax. + 44 1538 361330

Technical data sheet

2-Ethylhexyl acetate (2EHA)

Version: February 2009

Synonyms

2-Ethylhexyl acetate.

Formula

 $C_{10}H_{20}O_2$

Structural formula

Molecular weight: 172.27

CAS number

103-09-3

EINECS number

203-079-1

Product specification

Characteristics	Unit	Value	Method*
Appearance		Clear Liquid, free suspended matter	from Visual
Colour	APHA/Hazen	<=10	AM 018
Odour		Characteristic	AM 074
Acidity as acetic acid	%	<= 0,01	AM 006
Water content	%	<= 0,1	AM 023
Ester content	%	>= 99,0	AM 999

^{*} Internal methods available upon request.

Technical Data Sheet

Version: February 2009 Pag. 1 of 2



Polynt SpA – Headquarter

Via Enrico Fermi, 51 I-24020 Scanzorosciate (Bg) Italy Tel. +39 035 652770

Fax +39 035 652814

Polynt SpA

Via Abate Bertone, 10 13881 Cavaglià (BI) Italy Tel. +39 01 61996611 Fax. +39 01 61996623 Polynt UK Ltd

Station Road - Cheddleton Nr Leek Staffordshire ST13 7EF UK Tel. + 44 1538 369000 Fax. + 44 1538 361330

Typical properties

Characteristics	Unit	Value
Boiling point @ 760 mmHg	°C	199
Density @ 20 °C	g/ml	0.873
Melting Point	°C	-93
Flash point (closed cup)	°C	82

Main applications

Main applications for 2EHA:

- 2EHA is a high boiling ester, suitable for using in nitrocellulose and other synthetic lacquer formulation:
- 2EHA is an excellent film-forming agent in emulsion finishing for textiles, leather and similar products.

Handling

<u>Packaging:</u> Steel drums 180 kg net.

IBC 900 kg net

Bulk

Storage: The packaged material shall be kept into its original packaging, in cool

and well ventilated place, neither under rain nor in wet places, away from flames and heating sources. The bulk material shall be stored in stainless steel tanks, under nitrogen blanketing; for a long lasting quality the material shall be kept at ambient temperature (ideally not above 30°C)

and away from any flame or concentrated heat source

Shelf life: 5 years from production date.

Certifications: Kosher: UK

Halal: UK

The information contained in this sheet is correct and accurate and is based on our technical and scientific knowledge and on literature at the date of going to press. Such information relates only to use of the products in the pure state and for the purposes stated herein. Nothing stated here may be taken or construed as implying of any existing patents. Nor is any warranty, whether explicit or implicit, given with regard to results to be obtained through the use of the aforesaid information.

Version: February 2009 Pag. 2 of 2