Polynt S.p.A – Stab. Scanzorosciate Via Enrico Fermi, 51 I-24020 Scanzorosciate (Bg) Italy Tel. +39 035 652770 – Fax +39 035 652814



Technical data sheet

Methyltetrahydrophthalic anhydride NT-K1 (MTHPA NT-K1)

Version: February 2011

Chemical composition

Anhydride MTHPA NT-K1 is a pre-accelerated blend of cycloaliphatic anhydrides mainly based on MTHPA isomers.

Equivalent weight (theoretical): 167.3

Product specification

Characteristics	Unit	Value	Method*	Reference
Appearance		Clear liquid	L000	
Anhydride content	%	98.5 min	L001	
Colour	Gardner	4 max	GM011	ASTM D-1544
Acid content	%	0.5 max	L002	

^{*} Internal methods available upon request.

Typical properties

Characteristics	Unit	Value		
Viscosity @ 25°C	mPa.s	50 ÷ 100	G006	DIN 53015
Density @ 25°C	g/ml	1.195		
Vapour pressure @ 120°C	mmHg	2.0		
Refractive index n ²⁵ _D		1.4953		

Version: February 2011 Pag. 1 di 2

Polynt S.p.A – Stab. Scanzorosciate Via Enrico Fermi, 51 I-24020 Scanzorosciate (Bg) Italy Tel. +39 035 652770 – Fax +39 035 652814



Sede Legale Via Enrico Fermi, 51 I-24020 Scanzorosciate (BG) Tel. 035 652111 – Fax 035 652421

Main applications

MTHPA is mainly used as a curing agent for epoxy resins. It has a low tendency to absorb moisture from the air and zero or minimal formation of carbon dioxide when mixed with tertiary amine accelerators.

MTHPA can be easily blended with various liquid resins providing stable, low viscous mixtures and long pot lives. It is widely used for:

- Casting / Potting
- Impregnation
- Lamination

In the field of reinforced plastics it is used for filament winding products (pipes for oil, poles and sport goods), laminated sheets, printed circuit boards, switch gears.

Thanks to its excellent insulating properties, MTHPA found a lot of applications for the production of electrical parts such as: capacitors, resistors, wiring parts transformers, ignition coils, fly back transformers.

Handling

<u>Packaging:</u> Steel painted drum 220 kg;

bulk;

Upon request other form of packaging can be available.

Storage: It must be stored away from open flames or other potential ignition

sources, and should be protected from moisture because it easily

crystallizes when in contact with the air moisture.

During the winter season MTHPA can solidify, but it can be easily

remelted by simply heating.

Shelf life: 12 months from production date.

The information contained in this sheet is correct and accurate and is based on our technical and scientific knowledge and on literature at the date of going to press. Such information relates only to use of the products in the pure state and for the purposes stated herein. Nothing stated here may be taken or construed as implying of any existing patents. Nor is any warranty, whether explicit or implicit, given with regard to results to be obtained through the use of the aforesaid information.

Version: February 2011 Pag. 2 di 2