

Compounds Carbon Fiber





Contents

1. Production Sites	3
2. Polynt Reichhold Group.	3
3. Carbon Fiber Compounds	4
4. Polynt-SMCarbon®	5
5. Polynt-BMCarbon®	7
6. Polynt-RECarbon®	8
7. Polynt-UDCarbon®	9
8. Polynt-TXTCarbon®	10
9. Company Addresses	11

Production Sites





Polynt Composites Germany GmbH Polynt Composites Poland Sp. z o.o.

Polynt SpA (Italy)
Polynt Composites Korea Co., Ltd.

Polynt Reichhold Group

After the merger on May 2017 the new Polynt-Reichhold Group is a global Company in the Intermediates, Coating and Composite Resins, Thermoset Compounds, Gel-coats and niche Specialties.

This combination enhances the Group's leading position as a global vertically integrated specialty chemicals player, with significant global presence in Europe, North America and Asia, a strategy initiated by Polynt with the successful integration of PCCR and CCP in the last years and now further reinforced by Reichhold's global scale, extensive product portfolio and R&D competencies.

Polynt-Reichhold Group is known for its superior quality and impressive range of products and with its excellent distribution network it can provide first-class service to customers whatever their market. Customer Service and Technical Service teams are renowned for their customer focus, offering the best service even after products have left manufacturing.

The Group strives to keep customers satisfied, assisting them in producing premium quality products every time they use its products. Product innovation is important for the Group's business and it's the reason for which it constantly works with customers to find solutions to problems. Introducing new or improved products ensures that Polynt-Reichhold Group continue not only to deliver what the market wants and needs, but also when it is wanted and needed.

Carbon Fiber Compounds

Polynt Grroup offers a wide product range to meet the needs of the Carbon Fibers market, focusing its attention on the most important product properties - high performance, good aesthetics and varied technologies.

Carbon Fiber Compounds is a product family based on vinyl ester or epoxy resins reinforced with carbon fiber, which gives the material exceptional stiffness and resistance properties.


This family includes:

- Polynt-SMCarbon®
- Polynt-BMCarbon®
- Polynt-RECarbon®
- Polynt-UDCarbon®
- Polynt-TXTCarbon®



Since it is possible to use different technologies, Polynt Group's main sectors for carbon fiber reinforced compounds are automotive, aircraft, industrial, sport and leisure.

Product Mechanical Properties Overview: flexural modulus vs flexural strength



Polynt-SMCarbon®

Polynt-SMCarbon® is a sheet molding composites material reinforced with carbon fibers with lengths ranging from 12mm to 50mm. It is produced in sheets of 1000 mm width and 2-3 mm thickness and it can be packed in rolls or boxes per customer specifications.

Polynt-SMCarbon® is particularly suitable for compression molding of flat medium to large specifications.





Photo of the Mansory Stallone 812: the car body is entirely made in Polynt-SMCarbon®. Photo by *Mansory*




Photo of Dallara Stradale, the new road car of Dallara. Photo by *Dallara*

Polynt-SMCarbon® main features are:


- · the new chopped aesthetic surfaces
- versatility of technology (compression molding and autoclave)
- ability to adjust the formula in order to optimize the product for specific requests.

Polynt-SMCarbon [®] Family				
Resin Type	Series	CF Towtex	CF Content	Technology
Vinyl Ester	24 Series	3K	50% - 60%	
		12K	40% - 50% - 60%	Compression
		48K	50%	Molding
	24 LW Series	12K	25%	
	80 Series			Compression Molding
Ероху	85 Series	3K 12K	50% - 60%	Autoclave, Compression Molding
	90 Series			Autoclave

Polynt Group produces Polynt-SMCarbon® at the German site in Miehlen, by using two different resin systems: Vinyl Ester Resin and Epoxy Resin. Both charts show the most important Polynt-SMCarbon® peculiarity: modulus increases with CF content, strength increases with lower CF towtex.



Polynt-SMCarbon® 24
Tensile Modulus vs. CF content (12K)



Polynt-SMCarbon® 24
Tensile Strength vs. different CF towtex (%)

The two photos hereunder show:

On the left

Chopped carbon aesthetic on Aston Martin DB11: Polynt-SMCarbon® 90 CF60-12K processed by MATA Automotive

On the right

Luxury seats produced with Polynt-SMCarbon® 90 CF60 -12K using autoclave technology





Polynt-BMCarbon®

Polynt-BMCarbon® is a bulk molding composite material reinforced by short carbon fibers (6mm, 12mm).

It' is produced in granular and homogeneous bulk using Vynil Ester Resin or Epoxy Resin, it's packed in bags and it is particularly suitable for compression, transfer and injection molding.

Compared to the more common thermoplastic polymers, Polynt-BMCarbon[®] is a thermosetting compound with superior technical characteristics and performance:

- high mechanical properties in terms of rigidity and resistance
- · dimensional stability at high temperatures, due to the intrinsic nature of the thermoset materials
- · chemical and weathering resistance, especially formulated for outdoor applications
- · countless customization possibilities for specific requests.



On the left
Watch-case and cover
made of
Polynt-BMCarbon®.
Photo given by
15.48 WATCHES

On the right Scuba diving regulator made of Polynt-BMCarbon®. Photo given by Mares



Polynt-BMCarbon [®] Family				
Resin Type	CF Type	CF Content and Length	Technology	
Vinyl Ester	Virgin Fibers	60% - 6mm	Compression Molding	
		60% - 12mm		
	Recycled Fibers	60% - 12mm		
Ероху	Virgin Fibers	45% - 6mm		
		45% - 12mm		

For further information please contact us






Polynt-RECarbon®

Polynt-RECarbon[®] is the family of composites reinforced with fleece made of recycled carbon fiber with different surface weights (from 20 to 400 gr/m²).

These materials have been developed in response to the growing need for sustainability and recycling. Recycling is achieved by reusing carbon fiber residue from various sources.

Polynt-RECarbon® can be used as semi-structural materials and veil for optimized surfaces, and it is available for Compression Molding and Autoclave technologies.



Detail of recycled carbon fiber veil for surface improvement (20 gr/m

Polynt-RECarbon [®] Family			
Resin Type	CF Type	CF Surface weight	Technology
Vinyl Ester	Pyrolized	200 gr/m ²	Company Molding
	Not Pyrolized	400 gr/m ²	
	Veil	20 gr/m²	Compression Molding
Ероху	Pyrolized	200 gr/m ²	
		400 gr/m²	Compression Molding and Autoclave
	Not Pyrolized	200 gr/m ²	
		400 gr/m ²	

For further information please contact us



Example of BMW recycled carbon fiber.

Polynt-UDCarbon®


Polynt-UDCarbon® is the family of composites reinforced by continuous and aligned carbon fibers, characterized by extreme mechanical properties, high stiffness on 0° direction and the possibility to combine with Polynt-SMCarbon®.

Because of its high mechanical properties (modulus and strength), Polynt-UDCarbon® composites are

used in purely structural applications in the automotive and

industrial sectors.

On the right
Detail of mechanical test.
Below
The graph shows the high stiffness of Polynt-UDCarbon®.



Polynt-UDCarbon [®] Family				
Resin Type	CF Towtex	CF Content	Technology	
Vinyl Ester	12 K	60%	Compression Molding	
Ероху	12 K	60%	Compression Molding; Autoclave	

For further information please contact us

Polynt-TXTCarbon®

Polynt-TXTCarbon® is the family of carbon reinforced materials developed for the prepregs market.

They are used in autoclave and low compression molding; they feature good aesthetics, good mechanical properties and fast curing with Vinyl Ester Resin.

They are cured by applying heat and pressure to provide quality laminates with high stiffness and strength at low weights and they are supplied in rolls.



Detail of fabric twill 2/2 - 200 gr/m²

Polynt-TXTCarbon® Family			
Resin Type	Fabric Type	CF Surface weight	Technology
Vinyl Ester	Twill 2/2	200 gr/m ²	
		400 gr/m ²	Compression Molding
		600 gr/m ²	
Ероху	Twill 2/2	200 gr/m ²	Compression Molding, Autoclave
		400 gr/m ²	
		600 gr/m ²	/ tatoolavo

For further information please contact us

COMPANY ADDRESSES

EUROPE

GERMANY

Polynt Composites Germany GmbH

Kieselstraße 2 56357 Miehlen Germany

Phone: +49 6772 93210 Fax: +49 6772 6888 email: contact.DE@polynt.com

ITALY

Polynt S.p.A.

Via Caduti e Dispersi dell' Aeronautica, 18 24030 Brembate Sopra (BG) - Italy Phone: +39 035 62 31 00

Fax: +39 035 33 35 00 email: contact.IT@polynt.com

POLAND

Polynt Composites Poland Sp. z o.o.

ul. Grabska 11d 32-005 Niepołomice

Poland

Phone: +48 12 281 42 00 Fax: +48 12 281 42 01 email: contact.PL@polynt.it

ASIA PACIFIC

KOREA

Polynt Composites Korea Co., Ltd.

51, Wanju Sandan 4-ro, Bongdong-eup Wanju-gun - Jeollabuk-do, 55321

Korea

Phone: +82 63 260 2114
Fax: +82 63 261 6431
email: contact.KR@polynt.com

This brochure is intended to provide a comprehensive list of the products and services available from all business sectors in which are active the companies and/or corporations controlled, directly or indirectly, by Specialty Chemicals International Ltd (hereinafter referred to as «Polynt Group»). The information, recommendations, answers and/or opinions contained herein (which must be intended only for explanatory purposes) are aimed to assist customers on the basis of our technical and scientific knowledge as of today, taking into account that our products are intended for sale to industrial and commercial customers. However we require customers to inspect and test our products before use and to satisfy themselves as to contents and suitability for their applications: nothing herein shall constitute or shall be deemed to be any other warranty or a representation, express or implied, including merchantability or fitness for a particular purpose or results to be obtained from the use of such information, nor shall be taken or construed as infringing of any existing patents. Product names in capital letters are registered trademarks of the relevant member of Polynt Reichhold Group. © Polynt S.p.A. - January 2019

