

Technical Data Sheet (25-Series) (PPO-00-LAB-TDS-08)

Description

25-Series gelcoats are formulated from premium polyester resins and fire retardant additives to achieve optimal fire retardancy properties and low slow smoke development. They are suitable for applications requiring a surface with resistance to flame spread and smoke development.

Distinguishing Characteristics

Low flame spread Low smoke development

Application Techniques

- 1. Catalyzation with MEKP is recommended at levels of 1.0-1.5% for best results. Over or under catalyzation will inhibit the gelcoat cure.
- 2. Apply in several thin overlapping layers rather than a single thick coat to avoid porosity, sagging and trapped solvent.
- 3. Thinning is not recommended since it can cause drainage, solvent entrapment or inadequate cure.

Typical Properties

Viscosity4500-5000 cps. (10000-12000 cps brush viscosity)Gel Time (1%MEC-EX)12-15' (100gm mass @22°C).Specific Gravity1.25-1.35Note:Brush viscosity is noted by a B after the colour number (eg. 25-310B).

Typical Physical Properties (Casting)

Barcol Hardness	38
Tensile Elongation, %	3.1
Water Absorption, %	

Note: Although our data concerning the fire resistance properties of these gelcoats is believed to be reliable, we recommend that the customer determine the suitability of these products for applications requiring fire resistance.

Created by: Polynt Composites Canada Inc., 29 Regan Road, Brampton, Ontario L7A 1B2 905-495-0606

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee of representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence, or otherwise is limited to the purchase price of the material. Freedom to use any patent is not to be inferred from any statement contained herein.

Version: January 2015	Approved by: Marc Fedoration	Page 1 of 1
-----------------------	------------------------------	-------------

The electronic file of this Document on the K: drive on the Polynt server is the Controlled Document. The Document is "uncontrolled" if printed. The user is responsible to verify that a printed version is the current version before using.